


Rigid IMC

Insulated Threadless Bushings 150°C with Copper Lug for Rigid Conduit & IMC



Features

- The plastic liner won't chip, crack, swell or shrink. It resists corrosion, chemicals and temperature extremes
- Two set screws provided with each fitting locks bushing in any desired position
- UL Listed for use with copper or aluminum grounding conductors
- RoHS compliant

Standard Materials

- Body - Malleable Iron/ Ductile Iron
- Lug - copper
- Insuliner - PEI rated at 150° C
- Clamping screw - steel
- Set screw - steel

Standard Finish

- Body - zinc plated

Applicable Third Party Standards

- UL Standard: 467
- UL Standard: 514B
- Fed. Spec. A-A-5053A
- NEMA: FB-1
- UL Listed File # E212551

U.S. Patent No. 6.808.181

Catalog Number	Trade Size (in)	Lug Size (in)	Dim A (in)	Dim B (in)	Inner Pack	Master Pack	Weight Per C (lb)
BRC-50S-1CKON	½	4-14	1.063	0.688	100	500	9.9
BRC-75S-1CKON	¾	4-14	1.250	0.688	50	250	13.2
BRC-100S-1CKON	1	4-14	1.625	0.750	50	250	17.6
BRC-125S-1CKON	1¼	4-14	2.000	0.813	25	125	20.9
BRC-125S-2CKON	1¼	1/0-8	2.000	0.813	25	125	32.4
BRC-150S-1CKON	1½	4-14	2.313	0.813	25	125	25.3
BRC-150S-2CKON	1½	1/0-8	2.313	0.813	25	125	36.8
BRC-200S-1CKON	2	4-14	2.750	0.875	10	50	29.8
BRC-200S-2CKON	2	1/0-8	2.750	0.875	10	50	41.3
BRC-250S-2CKON	2½	1/0-8	3.313	1.000	-	10	66.5
BRC-250S-3CKON	2½	3/0-6	3.313	1.000	-	10	90.7
BRC-250S-4CKON	2½	250MCM-6	3.313	1.000	-	10	101.0
BRC-300S-2CKON	3	1/0-8	4.000	1.000	-	10	82.0
BRC-300S-3CKON	3	3/0-6	4.000	1.000	-	10	106.1
BRC-300S-4CKON	3	250MCM-6	4.000	1.000	-	10	116.4
BRC-350S-3CKON	3½	3/0-6	4.375	1.063	-	10	111.7
BRC-350S-4CKON	3½	250MCM-6	4.375	1.063	-	10	122.0
BRC-400S-3CKON	4	3/0-6	5.063	1.125	-	10	142.5
BRC-400S-4CKON	4	250MCM-6	5.063	1.125	-	10	152.8
BRC-500S-3CKON^	5	3/0-6	6.063	1.188	-	5	186.6
BRC-500S-4CKON^	5	250MCM-6	6.063	1.188	-	5	196.9
BRC-600S-3CKON^	6	3/0-6	7.188	1.188	-	5	224.1
BRC-600S-4CKON^	6	250MCM-6	7.188	1.188	-	5	234.4

^ 5 and 6 are NOT UL approved

