



Reducing Bushings for Threaded Rigid Conduit & IMC

Features

- RB1 thru RB13 - NPSM internal and external threads
- RB14 thru RB31 - NPT internal and external threads

Standard Materials

- RB1 thru 13 - Steel
- RB14 thru 31 - Malleable Iron /Ductile Iron

Standard Finish

- Zinc plated

Applicable Third Party Standards

- UL Standard: 514B
- Fed. Spec. A-A-50553
- NEMA: FB-1
- UL Listed File # E207875

Catalog Number	Trade Size (in)	Dim A (in)	Dim B (in)	Master Pack	Weight Per C (lb)
RB1KON	3/4 x 1/2	1.000	0.563	200	4.4
RB2KON	1 x 1/2	1.313	0.625	100	13.1
RB3KON	1 x 3/4	1.313	0.625	100	7.5
RB4KON	1 1/4 x 1/2	1.625	0.750	50	28.8
RB5KON	1 1/4 x 3/4	1.625	0.750	50	21.9
RB6KON	1 1/4 x 1	1.625	0.750	50	14.4
RB7KON	1 1/2 x 1/2	1.875	0.750	50	40.6
RB8KON	1 1/2 x 3/4	1.875	0.750	50	34.4
RB9KON	1 1/2 x 1	1.875	0.750	50	25.8
RB10KON	1 1/2 x 1 1/4	1.875	0.750	50	11.5
RB11KON	2 x 1	2.313	0.875	25	66.3
RB12KON	2 x 1 1/4	2.313	0.875	25	48.8
RB13KON	2 x 1 1/2	2.313	0.875	25	33.8
RB14KON	2 1/2 x 1	2.875	1.313	10	126.3
RB15KON	2 1/2 x 1 1/4	2.875	1.313	10	127.5
RB16KON	2 1/2 x 1 1/2	2.875	1.313	10	106.2
RB17KON	2 1/2 x 2	2.875	1.313	10	68.8
RB18KON	3 x 1	3.438	1.313	10	190.6
RB19KON	3 x 1 1/4	3.438	1.313	10	190.6
RB20KON	3 x 1 1/2	3.438	1.313	10	162.5
RB21KON	3 x 2	3.438	1.313	10	146.9
RB22KON	3 x 2 1/2	3.438	1.563	10	116.9
RB23KON	3 1/2 x 2	4.000	1.500	5	240.0
RB24KON	3 1/2 x 2 1/2	4.000	1.563	5	234.4
RB25KON	3 1/2 x 3	4.000	1.625	5	112.5
RB26KON	4 x 2	4.438	1.500	5	303.8
RB27KON	4 x 2 1/2	4.438	1.500	5	350.0
RB28KON	4 x 3	4.438	1.563	5	237.5
RB29KON	4 x 3 1/2	4.438	1.750	5	138.8
RB30KON	5 x 4	5.500	1.750	5	375.0
RB31KON	6 x 5	6.563	1.750	5	462.5

