



**Rigid Compression Couplings for
Threadless Rigid Conduit & IMC
Malleable Iron**

Features

- Concrete tight

Standard Finish

- Malleable Iron / Ductile Iron
- Zinc plated

Applicable Third Party Standards

- UL Standard: 514B
- Fed. Spec. A-A-50553
- NEMA: FB-1
- UL Listed File # E207875



Catalog Number	Trade Size (in)	Dim A (in)	Dim B (in)	Dim C (in)	Inner Pack	Master Pack	Weight Per C (LB)
RCK50KON	½	1.813	0.500	1.500	25	125	30.0
RCK75KON	¾	1.875	0.500	1.625	20	100	32.0
RCK100KON	1	2.188	0.563	2.000	10	50	43.7
RCK125KON	1¼	2.625	0.750	2.375	5	25	77.6
RCK150KON	1½	2.688	0.688	2.625	5	25	93.3
RCK200KON	2	3.063	0.938	3.313	2	10	159.2
RCK250KON	2½	4.500	2.000	3.750	2	10	276.5
RCK300KON	3	4.938	2.250	4.250	1	5	393.3
RCK350KON	3½	5.000	2.250	4.750	1	5	546.7
RCK400KON	4	5.313	2.438	5.313	1	5	626.1

