



### Set Screw Rigid Couplings Threadless for Rigid Conduit & IMC

#### Features

- Concrete tight when taped

#### Standard Materials

- Malleable Iron / Ductile Iron / Steel 2½" to 4"

#### Standard Finish

- Zinc plated

#### Applicable Third Party Standards

- UL Standard: 514B
- Fed. Spec. A-A-50553
- NEMA: FB-1
- UL Listed File # E207875



Catalog Number	Trade Size (in)	Dim A (in)	Dim B (in)	Dim C (in)	Inner Pack	Master Pack	Weight Per C (lb)
RSK50KON	½	1.750	0.780	1.375	20	100	23.6
RSK75KON	¾	2.000	0.875	1.563	20	100	35.1
RSK100KON	1	2.688	1.188	1.875	5	50	56.0
RSK125KON	1¼	2.750	1.250	2.188	5	25	68.1
RSK150KON	1½	3.188	1.500	2.500	5	20	91.7
RSK200KON	2	3.375	1.563	3.000	2	10	134.7
SK250RKON**	2½	3.130	4.000	-	-	8	130.0
SK300RKON**	3	3.750	4.250	-	-	6	140.0
SK350RKON**	3½	4.250	4.500	-	-	4	216.6
SK400RKON**	4	4.750	4.750	-	-	4	250.0
RSK500KON^A	5	6.000	2.813	6.500	-	1	1150.0
RSK600KON^A	6	6.500	3.000	7.500	-	1	1400.0

\*Furnished with four set screws  
^ 5" and 6" are NOT UL approved  
+Steel

