

## Form Aluminum Conduit Bodies

### Applications

To provide access to conductors for pulling, splicing and maintenance

### Features


- Tapered threaded hubs - NPT
- Suitable for use in concrete
- Wet location

### Standard Materials


- Die cast aluminum
- Covers - Stamped aluminum
- Gasket - Neoprene rubber

### Applicable Third Party Standards

- UL Standard: 514A
- Fed. Spec. A-A-50563
- NEMA: FB-1
- UL Listed File # E208392



ACKON



AC-CGKON

Cover & Gasket Included



Catalog Number	Trade Size (in)	Dim A (in)	Dim B (in)	Dim C (in)	Inner Pack	Master Pack	Weight Per C (lb)
<b>Aluminum Die Cast Threaded C Conduit Bodies</b>							
AC1KON	1/2	4.688	1.375	1.313	10	100	21.3
AC2KON	3/4	5.500	1.563	1.625	10	50	33.1
AC3KON	1	6.438	1.750	1.875	5	25	46.3
AC4KON	1 1/4	8.313	2.500	2.500	2	10	81.9
AC5KON	1 1/2	8.375	2.500	2.500	2	10	85.0
AC6KON	2	10.313	3.188	3.375	1	5	187.5
AC7KON	2 1/2	13.125	4.500	4.000	-	1	325.0
AC8KON	3	13.188	4.563	4.563	-	1	398.8
AC9KON	3 1/2	16.125	5.688	5.625	-	1	975.0
AC10KON	4	16.125	5.688	5.625	-	1	875.0
<b>Aluminum Die Cast Threaded C Conduit Bodies with Stamped Aluminum Cover and Neoprene Gasket</b>							
AC1CGKON	1/2	4.688	1.375	1.563	10	100	27.5
AC2CGKON	3/4	5.500	1.563	1.750	10	50	40.5
AC3CGKON	1	6.063	1.750	2.125	5	25	56.3
AC4CGKON	1 1/4	8.313	2.500	2.750	2	10	101.0
AC5CGKON	1 1/2	8.375	2.500	2.750	2	10	104.1
AC6CGKON	2	10.313	3.188	3.625	1	5	219.8
AC7CGKON	2 1/2	13.125	4.500	4.250	-	1	386.7
AC8CGKON	3	13.188	4.563	1.813	-	1	460.5
AC9CGKON	3 1/2	16.125	5.688	6.000	-	1	1098.2
AC10CGKON	4	16.125	5.688	6.000	-	1	998.2

