

Conduit Bodies, Covers, Gaskets

Form 5 Aluminum Conduit Bodies

Applications

To provide access to conductors for pulling, splicing and maintenance

Features

- Tapered threaded hubs - NPT
- Suitable for use in concrete
- Wet location

Standard Materials


- Die cast aluminum
- Covers - Stamped aluminum
- Gasket - Neoprene rubber

Applicable Third Party Standards

- UL Standard: 514A
- Fed. Spec. A-A-50563
- NEMA: FB-1
- UL Listed File # E208392




ALBKON



ALB-CGKON

Cover & Gasket Included



Catalog Number	Trade Size (in)	Dim A (in)	Dim B (in)	Dim C (in)	Inner Pack	Master Pack	Weight Per C (lb)
Aluminum Die Cast Threaded LB Conduit Bodies							
ALB1KON	½	4.313	1.313	2.188	10	100	24.3
ALB2KON	¾	5.063	1.563	2.438	10	50	37.2
ALB3KON	1	5.875	1.750	2.750	5	25	46.3
ALB4KON	1¼	7.813	2.500	3.438	2	10	97.7
ALB5KON	1½	7.813	2.500	3.438	2	10	90.9
ALB6KON	2	10.063	3.125	4.313	1	5	221.6
ALB7KON	2½	12.813	4.500	5.313	-	1	365.7
ALB8KON	3	12.813	4.500	5.813	-	1	429.7
ALB9KON	3½	15.625	5.563	7.063	-	1	936.9
ALB10KON	4	15.625	5.563	7.063	-	1	851.4
Aluminum Die Cast Threaded LB Conduit Bodies with Stamped Aluminum Cover and Neoprene Gasket							
ALB1CGKON	½	4.313	1.313	2.438	10	100	30.5
ALB2CGKON	¾	5.063	1.563	2.688	10	50	44.6
ALB3CGKON	1	5.875	1.750	3.000	5	25	56.3
ALB4CGKON	1¼	7.813	2.500	3.688	2	10	116.8
ALB5CGKON	1½	7.813	2.500	3.688	2	10	110.0
ALB6CGKON	2	10.063	3.125	4.563	1	5	253.9
ALB7CGKON	2½	12.813	4.500	5.563	-	1	427.4
ALB8CGKON	3	12.813	4.500	6.188	-	1	491.4
ALB9CGKON	3½	15.625	5.563	7.313	-	1	1060.1
ALB10CGKON	4	15.625	5.563	7.313	-	1	974.6