

Conduit Bodies, Covers, Gaskets

Form 5 Aluminum Conduit Bodies

Applications

To provide access to conductors for pulling, splicing and maintenance

Features

- Tapered threaded hubs - NPT
- Suitable for use in concrete
- Wet Location

Standard Materials


- Die cast aluminum
- Covers - Stamped aluminum
- Gasket - Neoprene rubber

Applicable Third Party Standards

- UL Standard: 514A
- Fed. Spec. A-A-50563
- NEMA: FB-1
- UL Listed File # E208392




ALLKON



ALL-CGKON

Cover & Gasket Included



Catalog Number	Trade Size (in)	Dim A (in)	Dim B (in)	Dim C (in)	Inner Pack	Master Pack	Weight Per C (lb)
Aluminum Die Cast Threaded LL Conduit Body							
ALL1KON	½	4.313	2.063	1.375	10	100	24.5
ALL2KON	¾	5.063	2.250	1.625	10	50	36.8
ALL3KON	1	5.875	2.625	1.875	5	25	45.2
ALL4KON	1¼	7.813	3.625	2.500	2	10	97.9
ALL5KON	1½	7.813	3.625	2.500	2	10	91.9
ALL6KON	2	10.603	4.438	3.375	1	5	245.0
ALL7KON	2½	12.813	5.750	4.000	-	1	387.6
ALL8KON	3	12.813	5.750	4.500	-	1	439.2
ALL9KON	3½	15.625	7.688	5.625	-	1	923.7
ALL10KON	4	15.625	7.688	5.625	-	1	881.8
Aluminum Die Cast Threaded LL Conduit Body with Stamped Aluminum Cover and Neoprene Gasket							
ALL1CGKON	½	4.313	2.063	1.625	10	100	30.7
ALL2CGKON	¾	5.063	2.250	1.875	10	50	44.2
ALL3CGKON	1	5.875	2.625	2.125	5	25	55.2
ALL4CGKON	1¼	7.813	3.625	2.750	2	10	117.0
ALL5CGKON	1½	7.813	3.625	2.750	2	10	111.0
ALL6CGKON	2	10.603	4.438	3.625	1	5	277.3
ALL7CGKON	2½	12.813	5.750	4.250	-	1	419.9
ALL8CGKON	3	12.813	5.750	4.750	-	1	500.9
ALL9CGKON	3½	15.625	7.688	5.875	-	1	1046.9
ALL10CGKON	4	15.625	7.688	5.875	-	1	1005.0