


ALRKON



ALR-CGKON



Form 5 Aluminum Conduit Bodies

Applications

To provide access to conductors for pulling, splicing and maintenance

Features

- Tapered threaded hubs - NPT
- Suitable for use in concrete
- Wet location

Standard Materials

- Die cast aluminum
- Covers - Stamped aluminum
- Gasket - Neoprene rubber

Applicable Third Party Standards

- UL Standard: 514A
- Fed. Spec. A-A-50563
- NEMA: FB-1
- UL Listed File # E208392

Catalog Number	Trade Size (in)	Dim A (in)	Dim B (in)	Dim C (in)	Inner Pack	Master Pack	Weight Per C (lb)
Aluminum Die Cast Threaded LR Conduit Bodies							
ALR1KON	1/2	4.313	2.063	13.375	10	100	22.7
ALR2KON	3/4	5.063	2.250	1.625	10	50	37.5
ALR3KON	1	5.875	2.625	1.875	5	25	48.7
ALR4KON	1 1/4	7.813	3.625	2.500	2	10	98.1
ALR5KON	1 1/2	7.813	3.625	2.500	2	10	93.9
ALR6KON	2	10.063	4.438	3.375	1	5	253.5
ALR7KON	2 1/2	12.813	5.750	4.000	-	1	366.2
ALR8KON	3	12.813	5.750	4.500	-	1	406.3
ALR9KON	3 1/2	15.625	7.688	5.625	-	1	928.1
ALR10KON	4	15.625	7.688	5.625	-	1	901.7
Aluminum Die Cast Threaded LR Conduit Bodies with Stamped Aluminum Cover and Neoprene Gasket							
ALR1CGKON	1/2	4.313	2.063	1.625	10	100	28.9
ALR2CGKON	3/4	5.063	2.250	1.875	10	50	44.9
ALR3CGKON	1	5.875	2.625	2.125	5	25	58.7
ALR4CGKON	1 1/4	7.938	3.625	2.750	2	10	117.2
ALR5CGKON	1 1/2	7.938	3.625	2.750	2	10	113.0
ALR6CGKON	2	10.063	4.438	3.625	1	5	285.8
ALR7CGKON	2 1/2	12.813	5.750	4.250	-	1	427.9
ALR8CGKON	3	12.813	5.750	4.750	-	1	468.0
ALR9CGKON	3 1/2	15.625	7.688	5.875	-	1	1051.3
ALR10CGKON	4	15.625	7.688	5.875	-	1	1024.9

