

ATBKON

Form 5 Aluminum Conduit Bodies

Applications

To provide access to conductors for pulling, splicing and maintenance

Features


- Tapered threaded hubs - NPT
- Suitable for use in concrete
- Wet Location

Standard Materials

- Die cast aluminum
- Covers - Stamped aluminum
- Gasket - Neoprene rubber

Applicable Third Party Standards

- UL Standard: 514A
- Fed. Spec. A-A-50563
- NEMA: FB-1
- UL Listed File # E208392



ATB-CGKON



Catalog Number	Trade Size (in)	Dim A (in)	Dim B (in)	Dim C (in)	Inner Pack	Master Pack	Weight Per C (in)
Aluminum Die Cast Threaded TB Conduit Bodies							
ATB1KON	½	4.750	1.375	2.125	10	100	29.1
ATB2KON	¾	5.500	1.563	2.675	10	50	42.3
ATB3KON	1	6.500	1.813	2.750	5	25	58.2
ATB4KON	1¼	8.250	2.438	3.500	2	10	110.3
ATB5KON	1½	8.250	2.438	3.500	2	10	108.8
ATB6KON	2	10.500	3.188	4.500	1	5	192.2
Aluminum Die Cast Threaded TB Conduit Bodies with Stamped Aluminum Cover and Neoprene Gasket							
ATB1CGKON	½	4.750	1.375	2.375	10	100	34.8
ATB2CGKON	¾	5.500	1.563	2.625	10	50	49.2
ATB3CGKON	1	6.500	1.813	3.000	5	25	67.7
ATB4CGKON	1¼	8.250	2.438	3.750	2	10	128.4
ATB5CGKON	1½	8.250	2.438	3.750	2	10	126.9
ATB6CGKON	2	10.500	3.188	4.750	1	5	222.5

