

Conduit Bodies, Covers, Gaskets

Form 5 Aluminum Conduit Bodies

Applications

To provide access to conductors for pulling, splicing and maintenance

Features

- Tapered threaded hubs - NPT
- Suitable for use in concrete
- Wet Location

Standard Materials


- Die cast aluminum
- Covers - Stamped aluminum
- Gasket - Neoprene rubber

Applicable Third Party Standards


- UL Standard: 514A
- Fed. Spec. A-A-50563
- NEMA: FB-1
- UL Listed File # E208392



AXKON



AX-CGKON



Catalog Number	Trade Size (in)	Dim A (in)	Dim B (in)	Dim C (in)	Inner Pack	Master Pack	Weight Per C (in)
Aluminum Die Cast Threaded X Conduit Bodies							
AX1KON	½	4.750	2.688	1.375	10	100	31.4
AX2KON	¾	5.500	3.000	1.625	10	50	47.1
AX3KON	1	6.500	3.500	1.875	5	25	61.9
AX4KON	1¼	8.250	4.500	2.500	2	10	117.7
AX5KON	1½	8.250	4.500	2.500	2	10	117.9
AX6KON	2	10.500	5.375	3.375	1	5	212.5
Aluminum Die Cast Threaded X Conduit Bodies with Stamped Aluminum Cover and Neoprene Gasket							
AX1CGKON	½	4.750	2.688	1.625	10	100	37.1
AX2CGKON	¾	5.500	3.000	1.875	10	50	54.0
AX3CGKON	1	6.500	3.500	2.125	5	25	71.4
AX4CGKON	1¼	8.250	4.500	2.750	2	10	135.8
AX5CGKON	1½	8.250	4.500	2.750	2	10	136.0
AX6CGKON	2	10.500	5.375	3.625	1	5	242.8