

Rigid IMC

Clamp Back Spacers for Rigid Conduit & IMC

Features

- Heavy-duty casting
- RoHS compliant

Standard Materials


- Malleable Iron / Ductile Iron

Standard Finish

- Zinc plated

Applicable Third Party Standards

- UL Standard: 2239
- UL Listed File # E213669



Catalog Number	Trade Size	Dim A (in)	Dim B (in)	Dim C (in)	Dim D (in)	Inner Pack	Master Pack	Weight Per C (lb)
CB50KON	½	2.000	1.000	0.500	0.313	25	250	8.4
CB75KON	¾	2.313	1.063	0.500	0.313	25	250	12.2
CB100KON	1	2.313	1.250	0.563	0.375	25	125	15.9
CB125KON	1¼	3.438	1.875	0.750	0.438	20	100	22.1
CB150KON	1½	3.813	1.875	0.813	0.438	10	100	35.4
CB200KON	2	4.750	1.938	1.000	0.563	10	50	50.5
CB250KON	2½	5.750	2.438	1.000	0.563	-	25	81.0
CB300KON	3	6.750	2.625	1.000	0.563	-	25	82.9
CB350KON	3½	7.125	2.875	1.063	0.750	-	20	148.2
CB400KON	4	8.813	3.063	1.063	0.750	-	10	198.9
CB500KON	5	10.125	3.750	1.188	0.750	-	10	343.8
CB600KON	6	12.188	4.000	1.500	0.750	-	10	418.6