

Cord Grip Fittings

Color-Coded 45° Cord Grip Strain Relief Connectors

Applications

To secure and seal cords or cables entering enclosures or raceways

Features

- Neoprene grommet for a moisture proof seal
- Simple installation, cord can be installed without disassembly of the fitting
- Liquidtight/Oiltight/Raintight
- Suitable for NEMA 4 enclosures and other wet locations
- Male tapered thread NPT

- Colored grommet allows for easy identification of cable range
- RoHS compliant

Standard Materials

- Malleable Iron / Ductile Iron body and gland Nut
- Neoprene grommet

Standard Finish

- Zinc plated body, gland nut

Applicable Third Party Standards

- UL Standard: 514B
- Fed. Spec. A-A-50552
- UL Listed File # E240397



Catalog Number	Trade Size (in)	Color Code (in)	Cable Range (in)		Inner Pack	Master Pack	Weight Per C (lb)
			Min.	Max.			
CG50-25045KON	½	Red	0.15	0.25	25	100	27.1
CG50-35045KON	½	White	0.25	0.35	25	100	26.9
CG50-45045KON	½	Blue	0.35	0.45	25	100	27.0
CG50-56045KON	½	Green	0.45	0.56	25	100	26.3
CG50-65045KON	½	Brown	0.55	0.65	25	100	26.2
CG75-25045KON	¾	Red	0.15	0.25	10	50	42.0
CG75-35045KON	¾	White	0.25	0.35	10	50	42.5
CG75-45045KON	¾	Blue	0.35	0.45	10	50	41.8
CG75-56045KON	¾	Green	0.45	0.56	10	50	41.8
CG75-65045KON	¾	Brown	0.55	0.65	10	50	41.2
CG75-75045KON	¾	Yellow	0.65	0.75	10	50	37.6
CG75-85045KON	¾	Purple	0.75	0.85	10	50	37.2
CG100-56045KON	1	Green	0.45	0.56	5	25	55.1
CG100-65045KON	1	Brown	0.55	0.65	5	25	55.6
CG100-75045KON	1	Yellow	0.65	0.75	5	25	54.4
CG100-85045KON	1	Purple	0.75	0.85	5	25	53.8
CG100-95045KON	1	Gray	0.85	0.95	5	25	63.1
CG100-105045KON	1	Black	0.95	1.05	5	25	62.1
CG125-85045KON	1¼	Purple	0.75	0.85	5	25	77.9
CG125-95045KON	1¼	Gray	0.85	0.95	5	25	77.8
CG125-105045KON	1¼	Black	0.95	1.05	5	25	78.8
CG125-115045KON	1¼	Orange	1.05	1.15	5	25	77.9
CG125-125045KON	1¼	Red	1.15	1.25	5	25	75.7
CG125-137545KON	1¼	White	1.25	1.375	5	25	75.9
CG150-105045KON	1½	Black	0.95	1.05	2	10	96.6
CG150-115045KON	1½	Orange	1.05	1.15	2	10	95.6
CG150-125045KON	1½	Red	1.15	1.25	2	10	95.3
CG150-137545KON	1½	White	1.25	1.375	2	10	94.8

This chart is intended for use as a guide only. Whenever possible, exact cord dimensions should be used. Allied Tube & Conduit assumes no liability for errors, omissions or dimensional changes which may result from changes in design, material or the manufacturing process and which may affect cord and fitting compatibility.