

Cord Grip Fittings



Color-Coded 90° Cord Grip Strain Relief Connectors

Applications

To secure and seal cords or cables entering enclosures or raceways

Features

- Neoprene grommet for a moisture proof seal
- Simple installation, cord can be installed without disassembly of the fitting
- Liquidtight/Oiltight/Raintight
- Suitable for NEMA 4 enclosures and other wet locations
- Male tapered thread NPT

- Colored grommet allows for easy identification of cable range
- RoHS compliant

Standard Materials

- Malleable Iron/Ductile Iron body and gland Nut
- Neoprene grommet

Standard Finish

- Zinc plated body, gland nut

Applicable Third Party Standards

- UL Standard: 514B
- UL Listed File # E240397
- Fed. Spec. A-A-50552

Catalog Number	Trade Size (in)	Color Code (in)	Cable Range (in)		Inner Pack	Master Pack	Weight Per C (lb)
			Min.	Max.			
CG50-25090KON	½	Red	0.15	0.25	25	100	29.2
CG50-35090KON	½	White	0.25	0.35	25	100	29.6
CG50-45090KON	½	Blue	0.35	0.45	25	100	29.0
CG50-56090KON	½	Green	0.45	0.56	25	100	29.0
CG50-65090KON	½	Brown	0.55	0.65	25	100	28.5
CG75-25090KON	¾	Red	0.15	0.25	10	50	46.4
CG75-35090KON	¾	White	0.25	0.35	10	50	48.3
CG75-45090KON	¾	Blue	0.35	0.45	10	50	45.4
CG75-56090KON	¾	Green	0.45	0.56	10	50	45.3
CG75-65090KON	¾	Brown	0.55	0.65	10	50	45.7
CG75-75090KON	¾	Yellow	0.65	0.75	10	50	45.7
CG75-85090KON	¾	Purple	0.75	0.85	10	50	42.7
CG100-56090KON	1	Green	0.45	0.56	5	25	66.1
CG100-65090KON	1	Brown	0.50	0.65	5	25	67.8
CG100-75090KON	1	Yellow	0.65	0.75	5	25	65.7
CG100-85090KON	1	Purple	0.75	0.85	5	25	63.7
CG100-95090KON	1	Gray	0.85	0.95	5	25	71.3
CG100-105090KON	1	Black	0.95	1.05	5	25	70.9
CG125-85090KON	1¼	Purple	0.75	0.85	5	25	87.4
CG125-95090KON	1¼	Gray	0.85	0.95	5	25	86.9
CG125-105090KON	1¼	Black	0.95	1.05	5	25	85.6
CG125-115090KON	1¼	Orange	1.05	1.15	5	25	87.2
CG125-125090KON	1¼	Red	1.15	1.25	5	25	86.4
CG125-137590KON	1¼	White	1.25	1.375	5	25	79.8
CG150-105090KON	1½	Black	0.95	1.05	2	10	114.4
CG150-115090KON	1½	Orange	1.05	1.15	2	10	113.8
CG150-125090KON	1½	Red	1.15	1.25	2	10	113.4
CG150-137590KON	1½	White	1.25	1.375	2	10	112.4

This chart is intended for use as a guide only. Whenever possible, exact cord dimensions should be used. Allied Tube & Conduit assumes no liability for errors, omissions or dimensional changes which may result from changes in design, material or the manufacturing process and which may affect cord and fitting compatibility.

