



BC75-2-STKON

Conduit Beam Clamps

Features

- Steel bolt - Case hardened
- Standard sizes 3/4" - 2 1/2"
- Jaw opening 9/16" - 1 1/4"

Standard Materials

- Malleable Iron / Ductile Iron
- ^Steel

Standard Finish

- Zinc plated

Applicable Third Party Standards

- UL Standard: 2239
- UL Listed File # E213669

Conduit Beam Clamps

Catalog Number	Trade Size (in)	Tap Size (in)	Jaw Opening (in)	Dim A (in)	Dim B (in)	Dim C (in)	Inner Pack	Master Pack	Weight Per C (lb)
BC75-1KON	3/4	10 - 24	0.563	1.250	1.125	0.875	25	100	15.7
BC75-2KON	3/4	1/4 - 20	0.563	1.250	1.125	0.875	25	100	15.7
BC75-2-STKON^	3/4	1/4 - 20	0.750	1.375	1.563	0.938	-	50	15.0
BC100-1KON	1	10 - 24	0.750	1.375	1.375	1.188	-	50	24.0
BC100-2KON	1	1/4 - 20	0.750	1.375	1.375	1.188	-	25	24.0
BC150KON	1 1/2	5/16 - 18	0.688	1.563	1.500	1.438	-	25	34.7
BC200-1KON	2	3/8 - 16	0.875	1.813	1.813	1.938	-	25	52.9
BC200-2KON	2	1/2 - 13	0.875	1.813	1.813	1.938	-	25	52.9
BC250KON	2 1/2	1/2 - 13	1.250	2.250	2.313	2.563	-	25	117.9

^UL Listing not applicable to these sizes

Catalog Number	Trade Size (in)	Screw Size (in)	Load Rating (lb)
BC75-1KON	3/4	1/4 - 20	50
BC75-2KON	3/4	1/4 - 20	50
BC75-2-STKON	3/4	5/16 - 18	-
BC100-1KON	1	5/16 - 18	60
BC100-2KON	1	5/16 - 18	60
BC150KON	1 1/2	3/8 - 16	80
BC200-1KON	2	3/8 - 16	100
BC200-2KON	2	1/2 - 13	100
BC250KON	2 1/2	1/2 - 13	200

