



Die Cast Conduit Hubs with Insulated Throat

Features

- Tapered threaded male hub NPT
- Compact
- Liquidtight/Raintight/Oiltight/Concrete tight
- Suitable for wet locations

Standard Materials

- Zinc Die Cast
- Insuliner - Polycarbonate

Standard Finish

- Vibratory Finish

Applicable Third Party Standards

- UL Standard: 514B
- UL Listed File E207875
- RoHS



| Catalog Number | Trade Size (in) | Dim A (in) | Dim B (in) | Inner Pack | Master Pack | Weight Per C (lb) |
|----------------|-----------------|------------|------------|------------|-------------|-------------------|
| NHUBD50-ICKON | ½ | 1.42 | 1.22 | 25 | 250 | 16.3 |
| NHUBD75-ICKON | ¾ | 1.61 | 1.50 | 25 | 150 | 26.5 |
| NHUBD100-ICKON | 1 | 1.87 | 1.89 | 25 | 100 | 36.3 |
| NHUBD125-ICKON | 1¼ | 2.01 | 2.24 | 10 | 60 | 44.2 |
| NHUBD150-ICKON | 1½ | 2.13 | 2.52 | 10 | 60 | 61.2 |
| NHUBD200-ICKON | 2 | 2.2 | 3.03 | 10 | 40 | 89.3 |
| NHUBD250-ICKON | 2½ | 2.64 | 3.54 | 2 | 12 | 156.5 |
| NHUBD300-ICKON | 3 | 2.64 | 4.17 | 2 | 12 | 175.5 |
| NHUBD400-ICKON | 4 | 2.7 | 5.35 | 1 | 6 | 256.8 |

