

Rigid IMC

Two Gang FS and FD Cast Device Boxes

Features

- Tapered threads (NPT with integral bushings)
- Two grounding screws located on top for easy access
- Suitable for use in wet locations when used with S1002GKON or S1002KON cover and GASK434KON gasket
- Suitable for concrete use

Standard Materials

- Grey Iron

Standard Finish

- Zinc plated

Applicable Third Party Standards


- UL 514A
- NEMA: FB-1
- UL Listed File # E208392



FS Type




FD Type



FSC Type



FDC Type



Catalog Number	Trade Size (in)	Dim A (in)	Dim B (in)	Dim C (in)	Master Pack	Weight Per C (lb)
FS12KON	1/2	5.125	4.625	2.063	1	297.0
FS22KON	3/4	5.125	4.625	2.063	1	300.1
FS32KON	1	5.125	4.625	2.063	1	316.6
FD12KON	1/2	5.125	4.625	2.875	1	368.6
FD22KON	3/4	5.125	4.625	2.875	1	375.0
FD32KON	1	5.125	4.625	2.875	1	376.1
FSC12KON	1/2	5.938	4.625	2.063	1	301.6
FSC22KON	3/4	5.938	4.625	2.063	1	315.1
FSC32KON	1	5.938	4.625	2.063	1	335.2
FDC12KON	1/2	5.938	4.625	2.875	1	405.1
FDC22KON	3/4	5.938	4.625	2.875	1	385.1
FDC32KON	1	5.938	4.625	2.875	1	417.6

Aluminum available upon request