

Conduit Bodies, Covers, Gaskets

Form 5 Conduit Bodies

Applications

- To provide access to conductors for pulling, splicing and maintenance

Features

- Tapered threaded hubs - NPT
- Suitable for use in concrete

Standard Materials

- Malleable Iron/Ductile Iron

Standard Finish


- Zinc plated with aluminum enamel paint

Applicable Third Party Standards


- UL Standard: 514A
- Fed. Spec. W-C-586D
- NEMA: FB-1
- UL Listed File # E208392



MLBKON



MCKON



Catalog Number	Trade Size (in)	Dim A (in)	Dim B (in)	Dim C (in)	Master Pack	Weight Per C (lb)
Threaded LB Conduit Bodies						
MLB1KON	1/2	4.680	1.313	2.063	10	70.6
MLB2KON	3/4	5.375	1.500	2.250	10	96.7
MLB3KON	1	6.190	1.813	2.625	5	142.7
MLB4KON	1 1/4	8.125	2.625	2.750	5	287.3
MLB5KON	1 1/2	8.125	2.625	2.813	5	331.5
MLB6KON	2	10.500	3.125	4.438	5	534.1
MLB7KON	2 1/2	13.625	4.313	5.375	1	1105.0
MLB8KON	3	13.875	4.130	5.875	1	1160.3
MLB9KON	3 1/2	16.250	5.625	6.875	1	1989.0
MLB10KON	4	16.625	5.625	7.188	1	2099.5
Threaded C Conduit Bodies						
MC1KON	1/2	5.375	1.313	1.375	10	98.2
MC2KON	3/4	6.000	1.500	1.688	10	118.4
MC3KON	1	7.063	1.813	1.875	5	169.7
MC4KON	1 1/4	9.000	5.625	2.750	5	309.4
MC5KON	1 1/2	9.000	2.625	2.813	5	368.3
MC6KON	2	11.500	3.125	3.313	5	552.5
MC7KON	2 1/2	15.000	4.313	3.875	1	1215.5
MC8KON	3	15.125	4.313	4.750	1	1436.5
MC9KON	3 1/2	18.125	4.875	5.625	1	2210.0
MC10KON	4	18.125	4.875	5.625	1	2320.5