



Screw-On, 90 Degree, Liquidtight Fitting



Non-Insulated



Insulated



Features

- No disassembly required for installation of Screw-On Liquidtight
- Tapered threaded male hub - NPT
- Compact, slim diameter
- Liquidtight/Raintight/Oiltight
- Suitable for wet locations
- Long ferrule prevents pullout and tight bend conduit pop-out
- RoHS compliant
- Use with Liquidtight Flexible Metal Conduit

Standard Materials

- Malleable Iron
- Nylon
- Steel ferrule
- Steel locknut

Standard Finish

- Zinc plated

Applicable Third Party Standards

- UL Standard: 514B
- Fed. Spec. A-A-50553
- NEMA: FB-1
- UL Listed File # E207875
- Suitable for use in the following hazardous locations under NEC, Class I, Division 2; Class II, Division 1 and 2; and Class III, Division 1 and 2

U.S. Patent No. 7.914.048

(Only Applicable 3/8" - 2")

Catalog Number	Trade Size (in)	Dim A (in)	Dim B (in)	Dim C (in)	Dim D (in)	Inner Pack	Master Pack	Weight Per C (lb)
90° Non Insulated								
LTQ3890KON	3/8	1.31	0.50	1.13	1.63	-	25	25.4
LTQ5090KON	1/2	1.44	0.50	1.25	1.63	-	25	28.9
LTQ7590KON	3/4	1.63	0.50	1.56	1.75	-	10	44.1
LTQ10090KON	1	2.31	0.63	1.81	2.13	-	10	74.5
LTQ12590KON	1 1/4	2.88	0.69	2.25	2.19	4	40	96.1
LTQ15090KON	1 1/2	2.69	0.75	2.44	2.50	3	30	121.6
LTQ20090KON	2	3.19	0.75	3.00	2.88	2	20	176.4
LT25090KON*	2 1/2	8.31	1.06	1.06	2.88	-	1	837.7
LT30090KON*	3	9.50	1.13	4.88	9.50	-	1	1234.6
LT35090KON*	3 1/2	7.44	1.19	5.44	11.88	-	1	1896
LT40090KON*	4	13.81	1.19	6.06	12.94	-	1	2381
90° Insulated								
LTQ3890-ICKON	3/8	1.31	0.56	1.13	1.63	-	25	25.7
LTQ5090-ICKON	1/2	1.44	0.56	1.25	1.63	-	25	29.2
LTQ7590-ICKON	3/4	1.63	0.56	1.56	1.75	-	10	44.6
LTQ10090-ICKON	1	2.31	0.69	1.81	2.13	-	10	75.3
LTQ12590-ICKON	1 1/4	2.88	0.75	2.25	2.19	4	40	97.1
LTQ15090-ICKON	1 1/2	2.69	0.81	2.44	2.50	3	30	122.5
LTQ20090-ICKON	2	3.19	0.81	3.00	2.88	2	20	178.2
LT25090-ICKON*	2 1/2	8.30	1.06	1.06	2.88	-	1	846.1
LT30090-ICKON*	3	9.50	1.13	4.88	9.50	-	1	1246.9
LT35090-ICKON*	3 1/2	7.44	1.19	5.44	11.88	-	1	1914.9
LT40090-ICKON*	4	12.81	1.19	6.06	12.94	-	1	2404.8

* Note: Standard Liquidtight Fitting

