



### Squeeze Connectors for Flex, AC, MC Cables

#### Applications

For armored cable, flexible metal conduit, interlocked metal clad cables, HCF cables

#### Features

- Male hub threads - NPSM
- RoHS compliant

#### Standard Materials

- Malleable Iron / Ductile Iron
- Steel locknut

#### Standard Finish

- Zinc plated

#### Applicable Third Party Standards

- UL Standard: 514B
- Fed. Spec. A-A-50552
- NEMA: FB-1
- UL Listed File # E238299 3/8" through 1/2"
- UL Listed File # E207875
- CSA 243470



Catalog Number	Trade Size (in)	Dim A (in)	Dim B (in)	Dim C (in)	Inner Pack	Master Pack	Weight Per C (lb)
<b>Non Insulated</b>							
MSC38KON	3/8	1.000	0.438	1.625	25	125	5.6
MSC50KON	1/2	1.000	0.438	1.625	25	125	13.3
MSC75KON	3/4	1.125	0.500	1.750	20	100	16.7
MSC100KON	1	1.125	0.563	2.125	10	50	25.9
MSC125KON	1 1/4	1.188	0.563	2.188	10	50	39.8
MSC150KON	1 1/2	1.875	0.625	2.250	5	25	63.0
MSC200KON	2	2.000	0.750	2.688	-	5	107.2
MSC250KON^	2 1/2	2.063	0.875	3.313	-	5	171.9
MSC300KON^	3	2.125	1.063	3.875	-	5	202.6
MSC350KON^	3 1/2	3.750	1.313	6.500	-	1	442.0
MSC400KON^	4	4.125	1.500	7.250	-	1	663.0
<b>Insulated</b>							
MSC38-ICKON	3/8	1.000	0.500	1.625	25	125	5.7
MSC50-ICKON	1/2	1.000	0.500	1.625	25	125	13.4
MSC75-ICKON	3/4	1.125	0.563	1.750	20	100	16.9
MSC100-ICKON	1	1.125	0.625	2.125	10	50	26.2
MSC125-ICKON	1 1/4	1.188	0.625	2.188	10	50	40.2
MSC150-ICKON	1 1/2	1.875	0.688	2.250	5	25	63.6
MSC200-ICKON	2	2.000	0.813	2.688	-	5	108.2
MSC250-ICKON^	2 1/2	2.063	0.938	3.313	-	5	173.6
MSC300-ICKON^	3	2.125	1.125	3.875	-	5	204.6
MSC350-ICKON^	3 1/2	3.750	1.375	6.500	-	1	446.4
MSC400-ICKON^	4	4.125	1.563	7.250	-	1	669.6

^ 2 1/2 to 4" zinc plated and painted  
Only for 3/8"

