

LLKON

## Form 7 LL Conduit Bodies

### Applications

To provide access to conductors for pulling, splicing and maintenance

### Features

- Tapered threaded hubs - NPT
- Suitable for use in concrete

### Standard Materials


- Cover and Clips - Steel
- Screws - Stainless Steel
- Gasket - Neoprene
- Body - Grey Iron

### Standard Finish

- Zinc plated with aluminum enamel paint

### Applicable Third Party Standards

- UL Standard: 514A
- Fed. Spec. A-A-50563
- NEMA: FB-1
- CSA 243470
- UL Listed File # E208392



LL-CGKON  
Cover & Gasket Included



## Threaded LL Conduit Bodies

| Catalog Number | Trade Size (in) | Dim A (in) | Dim B (in) | Dim C (in) | Master Pack | Weight Per C (lb) |
|----------------|-----------------|------------|------------|------------|-------------|-------------------|
| LL17KON        | ½               | 4.563      | 2.125      | 1.438      | 5           | 90.3              |
| LL27KON        | ¾               | 5.125      | 2.375      | 1.688      | 5           | 122.0             |
| LL37KON        | 1               | 6.063      | 2.688      | 1.875      | 5           | 159.2             |
| LL47KON        | 1¼              | 6.563      | 3.188      | 2.375      | 2           | 247.2             |
| LL57KON        | 1½              | 7.125      | 3.500      | 2.625      | 2           | 319.2             |
| LL67KON        | 2               | 8.125      | 4.125      | 3.250      | 2           | 472.6             |

## Threaded LL Conduit Bodies with Cover and Gasket

| Catalog Number | Trade Size (in) | Dim A (in) | Dim B (in) | Dim C (in) | Master Pack | Weight Per C (lb) |
|----------------|-----------------|------------|------------|------------|-------------|-------------------|
| LL17-CGKON     | ½               | 4.563      | 2.125      | 1.688      | 5           | 105.0             |
| LL27-CGKON     | ¾               | 5.125      | 2.375      | 1.938      | 5           | 140.6             |
| LL37-CGKON     | 1               | 6.063      | 2.688      | 2.125      | 5           | 207.4             |
| LL47-CGKON     | 1¼              | 6.563      | 3.188      | 2.688      | 2           | 277.0             |
| LL57-CGKON     | 1½              | 7.125      | 3.500      | 3.066      | 2           | 357.8             |
| LL67-CGKON     | 2               | 8.125      | 4.125      | 3.625      | 2           | 525.6             |

