


MLLKON



MLRKON



Form 5 Conduit Bodies

Applications

- To provide access to conductors for pulling, splicing and maintenance

Features

- Tapered threaded hubs - NPT
- Suitable for use in concrete

Standard Materials

- Malleable Iron/Ductile Iron

Standard Finish

- Zinc plated with aluminum enamel paint

Applicable Third Party Standards

- UL Standard: 514A
- Fed. Spec. A-A-50563
- NEMA: FB-1
- UL Listed File # E208392

Catalog Number	Trade Size (in)	Dim A (in)	Dim B (in)	Dim C (in)	Master Pack	Weight Per C (lb)
Threaded LL Conduit Bodies						
MLL1KON	½	4.688	2.063	1.375	10	87.9
MLL2KON	¾	5.375	2.250	1.688	10	110.3
MLL3KON	1	6.188	2.625	1.875	5	160.1
MLL4KON	1¼	8.125	2.750	2.750	5	346.9
MLL5KON	1½	8.125	3.500	2.813	5	369.0
MLL6KON	2	10.500	4.125	3.313	5	558.2
MLL7KON	2½	13.625	4.688	3.875	1	1211.3
MLL8KON	3	13.875	5.875	4.750	1	1542.8
MLL9KON	3½	16.250	6.125	5.625	1	2444.0
MLL10KON	4	16.250	6.938	5.625	1	2598.2
Threaded LR Conduit Bodies						
MLR1KON	½	4.688	2.063	1.375	10	82.9
MLR2KON	¾	5.375	2.250	1.688	10	115.6
MLR3KON	1	6.188	2.625	1.875	5	178.5
MLR4KON	1¼	8.125	2.750	2.750	5	368.0
MLR5KON	1½	8.125	3.500	2.813	5	382.8
MLR6KON	2	10.500	4.125	3.313	5	687.1
MLR7KON	2½	13.625	4.688	3.875	1	1211.3
MLR8KON	3	13.875	5.875	4.750	1	1542.8
MLR9KON	3½	16.250	6.125	5.625	1	2487.7
MLR10KON	4	16.250	6.938	5.625	1	2667.2

