



Straight, Tubular Steel, Liquidtight Fitting



Non-Insulated



Insulated

Features

- Tapered threaded male hub - NPT
- Compact, slim diameter
- Liquidtight/Raintight/Oiltight
- Suitable for wet locations
- Long ferrule prevents pullout and tight bend conduit pop-out
- RoHS Compliant
- Low cost
- Use with Liquidtight Flexible Metal Conduit

Standard Materials

- Steel
- Steel ferrule
- Steel locknut

Standard Finish

- Zinc plated
- Nylon

Applicable Third Party Standards

- UL Standard: 514B
- Fed. Spec. A-A-50553
- NEMA: FB-1
- Suitable for use in the following hazardous locations under NEC, Class I, Division 2; Class II, Division 1 and 2; and Class III, Division 1 and 2
- UL Listed File # E207875

Catalog Number	Trade Size (in)	Dim A (in)	Dim B (in)	Dim C (in)	Inner Pack	Master Pack	Weight Per C (lb)
Non-Insulated							
LT38STLKON	3/8	1.000	0.500	1.063	25	100	11.4
LT50STLKON	1/2	1.125	0.500	1.250	25	100	16.3
LT75STLKON	3/4	1.125	0.500	1.563	25	100	22.1
LT100STLKON	1	1.313	0.625	1.813	5	25	35.4
LT125STLKON	1 1/4	1.375	0.688	2.063	5	25	41.2
LT150STLKON	1 1/2	1.438	0.750	2.063	5	25	50.4
LT200STLKON	2	1.500	0.813	2.750	5	25	64.5
Insulated							
LT38STL-ICKON	3/8	1.000	0.563	1.063	25	100	11.7
LT50STL-ICKON	1/2	1.125	0.563	1.250	25	100	16.6
LT75STL-ICKON	3/4	1.125	0.563	1.563	25	100	22.6
LT100STL-ICKON	1	1.313	0.688	1.813	5	25	36.2
LT125STL-ICKON	1 1/4	1.375	0.688	2.063	5	25	42.4
LT150STL-ICKON	1 1/2	1.438	0.750	2.063	5	25	51.8
LT200STL-ICKON	2	1.500	0.813	2.750	5	25	66.0

