



### U-Bolts for Rigid Conduit, IMC & EMT

#### Applications

Designed to secure Rigid conduit, IMC, or EMT perpendicular to beam, channel and angle supports

#### Features

- Two hex nuts
- RoHS compliant

#### Standard Materials

- Steel U-Bolts and nuts

#### Standard Finish

- U-Bolt - Mechanically galvanized

#### Applicable Third Party Standards

- UL Standard: 2239
- UL Listed File # E213669



Catalog Number	Trade Size (in)	Thread Size (in)	Dim A (in)	Dim B (in)	Dim C (in)	Dim D (in)	Inner Pack	Master Pack	Weight Per C (lb)
SUBM50KON	1/2	5/16 - 18	1.000	1.250	2.500	1.813	100	1000	12.5
SUBM75KON	3/4	5/16 - 18	1.125	1.375	2.813	1.813	100	500	15.6
SUBM100KON	1	5/16 - 18	1.375	1.625	3.063	1.813	50	500	15.7
SUBM125KON	1 1/4	5/16 - 18	1.750	2.000	3.188	1.813	50	250	15.8
SUBM150KON	1 1/2	5/16 - 18	2.000	2.375	3.500	1.813	-	25	18.8
SUBM200KON	2	3/8 - 16	2.500	2.500	4.500	2.625	-	25	31.3
SUBM250KON	2 1/2	3/8 - 16	3.000	3.250	4.875	2.625	-	25	31.4
SUBM300KON	3	3/8 - 16	3.625	3.875	5.375	2.625	-	25	37.5
SUBM350KON	3 1/2	3/8 - 16	4.063	4.563	5.875	2.625	-	20	40.6
SUBM400KON	4	3/8 - 16	5.313	5.063	6.688	2.625	-	10	43.4

