

PVC COATED SEALING FITTINGS . EZS FEMALE HUBS

Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior Urethane coating thickness is a minimum 0.002"
- Sizes available are 1/2" to 3"
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes 1/2" - 2"
- For sizes 2 1/2" - 3", the length of the sleeve extension(s) shall be at least 2"
- Mating sealing forms are provided on all caps

Applications:

Allied Tube & Conduit® PVC Coated Sealing Fittings are used in hazardous locations to prevent flame and gas from continuing to travel through the conduit system. PVC coating provides corrosion protection. A sealing compound should be used on the interior after wiring. Compound supplied by the original fitting manufacturer.

Standards:

- NEC/CEC:
EZS 1-8
Class I, Division 1 & 2,
Groups C, D Class III
- UL Standard: 1203
- CSA Standard: C22.2



Item Number	Trade Size (in)	Weight per 100 (lbs)	A (in)	B (in)	Turning Radius (in)
For Sealing in Any Position					
PV0500EZS1	1/2	200	4.19	3.71	1.88
PV0700EZS2	3/4	230	4.19	3.71	1.88
PV1000EZS3	1	270	4.94	4.05	2.13
PV1200EZS4	1 1/4	350	5.06	4.49	2.31
PV1500EZS5	1 1/2	400	5.19	4.64	2.34
PV2000EZS6	2	820	7.06	5.49	3.28
PV2500EZS7	2 1/2	850	7.94	5.92	3.38
PV3000EZS8	3	900	8.63	6.58	3.88

