

PVC COATED MOGUL FITTINGS - BC

Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior Urethane coating thickness is a minimum 0.002"
- Sizes available are 1" to 4"
- Sealing sleeves on all hubs

Applications:

Allied Tube & Conduit® PVC Coated Mogul Style Conduit Bodies are used where an extra larger wiring space is required. They are available in all styles. Sealing mating between cover and fittings are provided.

Standards:

- UL Standard 514B
- CSA Standard: C22.2 No. 18



BC							
Part Number	Trade Size (in)	A (in)	B (in)	C (in)	D (in)	E (in)	Weight per 100 (lbs)
PV1000BC3	1	7.31	1.92	2.27	1.88	6	3.2
PV1200BC4	1¼	8.50	2.35	2.27	1.88	6	4.0
PV1500BC5	1½	10.38	2.60	3.08	2.63	10	5.9
PV2000BC6	2	12.25	3.17	3.08	2.63	10	7.8
PV2500BC7	2½	15.63	3.67	4.33	3.81	15	12.5
PV3000BC8	3	15.63	4.42	4.33	3.81	15	17.0
PV3500BC9	3½	18.75	4.92	5.33	4.75	20	25.0
PV4000BC10	4	18.75	5.42	5.33	4.75	20	28.0

