

PVC COATED STRUT

Features:

- Exterior PVC coating thickness is a minimum 0.02"
- 3 trade sizes and 5 standard styles

Applications:

Allied Tube & Conduit® PVC Coated Strut is a versatile system of structural elements that can be used to build supports for a variety of applications used in mechanical and electrical installations. Allied Tube & Conduit® offers 5 standard styles of strut: Standard, Back to Back, Slotted Standard, Shallow and Slotted Shallow.



Standard



Back to Back



Slotted Standard

Item Number	Trade Size (in)	Gauge Metal	Weight per 100 (lbs)	Standard Pack
PV0000B22	1 $\frac{5}{8}$ X 1 $\frac{5}{8}$	Standard	12 ga.	200
PV0000B22A	1 $\frac{5}{8}$ X 3 $\frac{1}{4}$	Back to Back	12 ga.	380
PV0000B22SH	1 $\frac{5}{8}$ X 1 $\frac{5}{8}$	Slotted Standard	12 ga.	185
PV0000B52	1 $\frac{5}{8}$ X 7 $\frac{7}{8}$	Shallow	12 ga.	135
PV0000B52SH	1 $\frac{5}{8}$ X 7 $\frac{7}{8}$	Slotted Shallow	12 ga.	130

