

PVC COATED PIPE STRAPS & CLAMP BACK SPACERS

Features:

- Exterior PVC coating thickness is a minimum 0.020"
- Sizes available are ½" to 4"

Applications:

Allied Tube & Conduit® PVC Coated Pipe Straps are used to securely mount conduit to a wall or other structure for support. They are available in two styles: one-hole malleable iron strap or two-hole stamped steel strap. Clamp backs are used to space the conduit from a wall or structure.



1 HOLE MALLEABLE STRAPS



2 HOLE STRAPS



CLAMP BACK

Part Number	Trade Size (in)	Weight / 100 (lbs)	Part Number	Trade Size (in)	Weight / 100 (lbs)	Part Number	Trade Size (in)	Weight / 100 (lbs)
PV05001S00	½	110	PV05002S00	½	200	PV0500CB1	½	10
PV07001S00	¾	140	PV07002S00	¾	300	PV0700CB2	¾	10
PV10001S00	1	120	PV10002S00	1	400	PV1000CB3	1	10
PV12001S00	1¼	250	PV12002S00	1¼	450	PV1200CB4	1¼	20
PV15001S00	1½	360	PV15002S00	1½	500	PV1500CB5	1½	20
PV20001S00	2	710	PV20002S00	2	1000	PV2000CB6	2	30
PV25001S00	2½	1110	PV25002S00	2½	1300	PV2500CB7	2½	100
PV30001S00	3	1340	PV30002S00	3	1700	PV3000CB8	3	170
PV35001S00	3½	1660	PV35002S00	3½	2000	PV3500CB9	3½	190
PV40001S00	4	2560	PV40002S00	4	2500	PV4000CB10	4	200

All dimensions are for informational purposes only *Tolerances +/- 5%

